Cleaner, Snother, Faster Plasma Cuting Brought to you by MOTOR GUARD

MODEL M-26 COMPRESSED AIR FILTER REPLACEMENT FILTER ELEMENT: M-723 SUGGESTED CHANGE INTERVAL: ONCE PER WEEK MOTOR GUARD CORPORATION MANTECA, CALIFORNIA 209-239-9191

MOTOR GUARD CORPORATION

580 CARNEGIE STREET PHONE (800) 227-2822 MANTECA, CA 95337 FAX (800) 237-7581 MADE IN U.S.A. www.motorguardplasma.com

MOTOR GUARD CORPORATION

Contaminants in your compressed air system dust, scale, condensed moisture and oil mist seriously effect the quality of your plasma cuts. Installation of a Motor Guard Sub-Micronic Air Filter on your plasma machine will effectively remove these contaminants; eliminating arc sputter and producing cleaner faster smoother cuts. In addition, Motor Guard filters virtually pay for themselves by reducing wear and prolonging the life of expensive tips and electrodes.

M-26 / M-60 Sub-Micronic Compressed Air Filter

- Cleaner, faster, smoother plasma cutting with ultra-clean air
- Prolongs the life of expensive plasma gun tips
 Removes oil aerosols, condensed moisture and particulates
- Installs on or near equipment for ultimate protection
- Ideal for plasma cutters and all air consuming equipment

D-13 Disposable Sub-Micronic Air Filter

MUTOR GUARD CORP. MANTECA. CA 95337

D-13

Ideal for small plasma cutters, air tools, blow guns and spray equipment

OTOR GUARD COR

- Removes oil aerosols, condensed moisture and particulates
- Lightweight and disposable
- Mounts directly on tool for ultimate protection

DD-1008 Disposable In-Line Desiccant Filter

Unique point-of-use desiccant dryer

- Ideal for small plasma cutters, air tools, blow guns and spray equipment
- Removes oil aerosols, condensed moisture and particulates
- Exclusive color-change indicator signals when replacement is needed
- Mounts directly on tool for ultimate protection

M-723 Replacement Filter Element for M-26/M60



| SPECIFICATIONS | | | | | | | | |
|----------------|--|--------------|---------------------|-----------------|-------------|-------------------------|-----------------|------------------------|
| PART # | DESCRIPTION | PIPE SIZE | MAX FLOW @80 PSI | MAX PRESSURE | MAX TEMP | REMOVAL RATING (Nom) | SIZE | REPLACEMENT Element |
| M-26 | Sub-Micronic Compressed Air Filter Mounting bracket included | 1/4" NPT | 2700 SCFH | 125 PSI | 175 F | .01 Microns | 5" x 7" | M-723 |
| M-60 | Sub-Micronic Compressed Air Filter Straight-through piping design | 1/2" NPT | 6000 SCFH | 125 PSI | 175 F | .01 Microns | 5" x 7" | M-723 |
| D-13 | Disposable Sub-Micronic Air Filter | 1/4" NPT | 1800 SCFH | 100 PSI | 175 F | .01 Microns | 2-1/2" x 3" | None |
| DD-1008 | Disposable In-Line Desiccant Filter | 1/4" NPT | 1200 SCFH | 100 PSI | 120 F | 5 Microns | 1-1/2" x 3-1/2" | None |



BBS-1 Scuff Pad Backer Block for Fast and Even Scuffing

- Never hand scuff again
- Applies even pressure over entire surface, eliminating finger stripes
- Soft and Flexible, conforms to curved or irregular surfaces
- Power hooks firmly retain scuff pad during vigorous use
- Designed to use one half of standard scuff pad